

[illegible]

1. THE HYDRANT SHALL BE AMERICAN DAPLUNG HYDRANT MODEL NO. B-62-B-5 OR AS SPECIFIED BY TOWN WITH NATIONAL STANDARD THREADED HOSE NOZZLES AND ONE 4-1/2" NATIONAL STANDARD THREADED PUMPER NOZZLE. NOZZLES SHALL BE FIELD REPLACEABLE. THE HYDRANT SHALL HAVE A MINIMUM VALVE OPENING OF 5-1/4" AND HAVE A MECHANICAL JOINT NUT. HYDRANT SHALL OPEN COUNTERCLOCKWISE (LEFT) AND SHALL BE BATTED OR 250 PSIG WORKING PRESSURE.
2. RESTRAINING GLANDS OR RESTRAINING GLANDS AND THE RODS (COMBINATION) SHALL BE USED AT ALL LOCATIONS WHERE RESTRAINTS ARE REQUIRED.
3. IF EVIDENCE OF GROUND WATER IS ENCOUNTERED, HYDRANT DRAIN HOLES SHALL BE PLUGGED.
4. ALL VALVES TO BE INSTALLED IN THE SAME MANNER AS INDICATED ON THE STANDARD DRAWINGS. VALVES THAT THEY MUST BE POURED AFTER USE.
5. ALL VALVES TO BE INSTALLED IN THE SAME MANNER AS INDICATED ON THE STANDARD DRAWINGS. VALVES THAT THEY MUST BE POURED AFTER USE.
6. ALL VALVES TO BE INSTALLED IN THE SAME MANNER AS INDICATED ON THE STANDARD DRAWINGS. VALVES THAT THEY MUST BE POURED AFTER USE.

NON-RISING STEM WITH 2" SQUARE NUT, VALVE TO OPEN BY TURNING LEFT (COUNTER CLOCKWISE). VALVES TO COMPLY WITH AWWA C-509. VALVES SHALL BE AS MANUFACTURED BY US PIPE OR APPROVED EQUAL

